

# PowerScan® 2D Imager

Industrial Strength Imaging Scanner

# Data Sheet



## Mechanical

Dimensions: 2.7 x 4.4 x 7.2" (6.9 x 11.2 x 18.3 cm)

Weight: 9.6 oz. (272 g) without cable

## Electrical

Operating voltage: 4 VDC to 14 VDC

Operating Current (maximum)

Interlaced Aiming: 275 mA @ 5V

Concurrent Aiming: 450 mA @ 5 V

Standby Current (maximum)

Normal Mode: 60 mA @ 5.5V

Low Power Mode: 30 mA @ 5.5V

## Environmental

Temperature rating

Operating: 14° to 122° F (-10° to 50° C)

Storage: -40° to 158° F (-40° to 70° C)

Humidity: 5 to 95% NC

Shock: Withstands Multiple 6.5' (2 m) drops to concrete

Vibration: Meets MIL-STD-810E

Water & Dust: IEC529 Rating IP54DW

## Optical

Light sources

Red Illumination LEDs: 626nm ± 30nm

Green Aiming LEDs: 520nm ± 30nm

Imager Resolution: VGA, 640 x 480 pixels

Pitch: ± 40°

Skew: ± 40°

Ambient Light Capability: 535 to 100,000 Lux

Depth of Field: See Depth of Field Table below

DEPTH OF FIELD  
Typical Range Comparisons

LABEL DENSITY	SR MODELS	HD MODELS
75 mil Linear	—	15 - 55"/38 - 140 cm
8 mil Linear	2.5 - 6.6"/6.4 - 16.8 cm	—
13 mil UPC	15 - 115"/3.8 - 29.2 cm	1.3 - 7.9"/3.3 - 20.1 cm
6.6 Mil PDF417	3.5 - 5.3"/8.9 - 13.5 cm	1.8 - 5.0"/4.6 - 12.7 cm
15 mil Data Matrix	2.7 - 5.5"/6.9 - 15.0 cm	1.3 - 5.0"/3.3 - 12.7 cm
35 mil Maxi Code	1.0 - 12.0"/2.5 - 30.5 cm	1.0 - 9.0"/2.5 - 22.9 cm

Minimum distance determined by symbol length and scan angle.  
Printing resolution, contrast, and ambient light dependent.

## Decoding Capability

Linear

- Code 11
- Code 28
- UPC/EAN/JAN
- RSS
- Code 39
- Codabar
- Interleaved 2 of 5
- Many Others
- Code 93
- Code 2 of 5

2D

- PDF417
- Maxicode
- Aztec Mesas
- Aztec
- MicroPDF
- Data Matrix
- EAN-UCC
- Others
- Code 49
- QR Code
- Composites

Postal Codes

- Postnet
- Canadian Post
- British Post
- China Post
- Japanese Post
- Others
- KIX
- Planet Code

OCR

- OCR-A
- OCR-B
- Others

Host Communications RS232C and USB

Warranty 3 Years

## Accessories

P/N: 7-0462	Universal Kit	P/N: 7-0430	Holster/Fork Lift Mount
P/N: 11-0070	Scan Stand	P/N: 7-0404	Take Up Reel



## Safety & Regulatory

Electrical: Complies to TÜV; UL; cUL

Emissions: Complies to FCC; EN 55022-B, CNS13438; AS/NZS 3548; VCCI



PSC Inc.  
959 Terry Street  
Eugene OR 97402-9150 USA  
Tel: 800 695 5700 or 541 683 5700  
Fax: 541 345 7140



Product specifications are subject to change without notice.

Additional information concerning this product or other PSC products and services can be found at the PSC web site: [www.psc.com](http://www.psc.com).

PSC, PowerScan, and the PSC logo are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners.

