

# Polycom® KIRK® Base Station

## **System Capacity**

- Max. number of speech channels: 4
- Circular coverage area: Typical range indoor: 20-50 m, outdoor: 600 m

## **Radio Interface**

- Average transmit power: typical 10mW/ch. (EU DECT), 5mW/ch. (US DECT)
- Peak transmit power: typical 250mW (EU DECT), 125mW (US DECT)
- Receiver sensitivity: typical -90 dBm.
- Frequency Bands available:
  - EU DECT (1880-1900 MHz)
  - US DECT (1920-1930 MHz)
  - Other DECT frequency bands are also available on request

## **Radio Approvals**

- EN 301 406 V1.5.1 (EU DECT)
- FCC RULES PART 15/Subpart D, RSS-213 (US DECT)

## **Electro Magnetic Compatibility (EMC) Approvals (Regulatory EU DECT Standards)**

- EN 301 489-1
- EN 301 489-6

## **Safety (Regulatory Standards)**

- UL60950-1 CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1: 2006

## **Environmental Conditions of the Installation Area**

- Relative humidity: Between 20% and 80% (non-condensing)
- Temperature range: Between 0°C and +55°C/32°F and 131°F.
- The equipment is in compliance with the requirements of EU directive 2002/95/EC (ROHS) and 2002/96/EC (WEEE)

## **Electrical Requirements**

- Power consumption: 0.98W (Max. 1.23W)
- The power supply is 48 VDC, 21mA (Powered from the server)

## **Physical Characteristics**

- Size (W: 10.0 x H: 3.0 x D: 10.0 cm)
- Weight: 113 g
- Grey-white (NCS 0502-Y)
- Wall-mountable, indoor

©2008 Polycom, Inc. All rights reserved.  
Polycom and the Polycom logo design are registered trademarks of  
Polycom, Inc. in the U.S. and various countries. All other trademarks  
are the property of their respective owners. Information in this  
document is subject to change without notice.